

POP WOODY

Bench

FREZZA



TECHNICAL DATA

structure

metal leg support: consisting of a 1.5 mm thick single square section steel bar (W. 1"3/4 D. 1"3/4) with rounded edges, laser cut, bent and welded to form the uprights (inclined at 97° to the beam) and the upper beam. A 5-mm thick steel sheet plate (W. 1"5/8 D. 1"5/8) with a central hole (for fixing the leg with a screw) is welded inside the upright. Four U-shaped brackets (W. 3"3/4 D. 4"1/8 H. 1"7/8) made of 2 mm thick steel sheet are welded to the beam and are used to attach the longitudinal beams and support the worktops. All metal parts are powder coated with an embossed finish.

leg: in natural ash with transparent acrylic varnish. The leg is inclined at 97°. The upper part is milled to fit inside the upright, where it is secured with two-component adhesive and screws. A PE-coated aluminium foot (Ø 1"1/8) is screwed into the lower end of each leg, allowing for + 10 mm adjustment for floor levelling.

longitudinal beams: each work surface is supported by two beams made from 1.5 mm thick steel bars (W. 1" 3/4 D. 1" 3/4) with rounded edges, which are attached to the leg brackets. All metal parts are powder-coated. In the bench configuration with a load-bearing service cabinet, a 3 mm thick steel sheet bracket is fastened to the latter to attach the beams and support the worktop. The bracket is fixed to the cabinet with wooden screws and telescopic screws.

Intermediate leg (for connecting several benches in line with each other): consisting of a steel section bar beam with a 1,5 mm thick 80x40 rectangular cross-section with rounded edges, closed at the ends by plastic caps. 2 uprights are screwed under the frame by means of a 4 mm thick steel plate, made of 1.5 mm thick square-section steel bars (W. 1" 3/4 D. 1" 3/4) with radiused edges. On the inner side of the uprights there are slots for the application of an optional inspectable carter with the purpose of concealing the cable descent. A pair of "U" brackets made of 2 mm thick steel sheet are welded on the beam, which is used to attach the longitudinal beams and support the worktops. Each bracket has two fixing positions for the beams, so that the desks can be mounted adjacent to or detached from each other. The lower ends of the uprights are equipped with feet (Ø 1" 3/4) made of polyethylene-coated steel, screwed onto polyethylene tips that are press-fitted into the base. The feet allow ±10 mm adjustment for floor levelling. All metal parts are painted with powders with an embossed finish.

top melamine: 18 mm thick chipboard (density 720 kg/m³, formaldehyde emission compliant with EU Regulation 2023/1464 and EPA TSCA Title VI), faced with anti-reflex melamine resins and edged with ABS (2 mm th. with rounded edges) with matching or contrasting edge. The top is equipped with threaded inserts for attachment to the structure and for fixing the screens. The top is fixed with screws to the brackets which create a 5 mm gap between the top and the structure.
H floor-to-top: 29"1/8

melamine with tilting cover (RIBA): in 18-mm thick chipboard (density 720 kg/m³, formaldehyde emission compliant with EU Reg. 2023/1464 and EPA TSCA Title VI), finished with anti-reflex melamine resins and edged in ABS (thickness 2 mm with rounded edges) with matching or contrasting edge. The top is equipped with threaded inserts for attachment to the structure and for fixing the screens. The top is fixed with screws to the brackets and to the beam supports, which create a 5 mm space between the top and the leg beam. On the tops there is a cover made of extruded anodised aluminium, closed at the ends by a pair of transparent ABS caps. The overall length is equal to that of the top. The covers are equipped with hinges (fixed to the central profile) that allow them to rotate (max. opening 90°). When rotated, the cover provides access to the cable tray below. A dust brush covers the cable passage between the cover and the top. A pair of 2 mm thick powder-coated steel brackets are fixed under the top (W. 15"3/4 D.1"5/8 H.5/8"), which serve as a support base for the cover (limiting its movement when closing) and for supporting the central profile. The use of the tilting cover requires the use of the central screen guide.
H floor-to-top: 29"1/8

free-standing bench module dimensions	W	D	H	W	D	H
	47"1/4	65"	29"1/8	39"3/8	49"1/4	29"1/8
	55"1/8	65"	29"1/8	47"1/4	49"1/4	29"1/8
	63"	65"	29"1/8	55"1/8	49"1/4	29"1/8
	70"7/8	65"	29"1/8	63"	49"1/4	29"1/8
bench modules: initial, intermediate and ending	78"3/4	65"	29"1/8	70"7/8	49"1/4	29"1/8

free-standing RIBA bench modules dimensions	W	D	H
	47"1/4	65"	29"1/8
	55"1/8	65"	29"1/8
RIBA bench modules: initial, intermediate and ending	63"	65"	29"1/8
	70"7/8	65"	29"1/8
	78"3/4	65"	29"1/8

lateral workstation dimensions: initial and ending	W	D	H	W	D	H
	23"5/8	65"	29"1/8	23"5/8	49"1/4	29"1/8
	31"1/2	65"	29"1/8	31"1/2	49"1/4	29"1/8

leg and beam finishes

metal legs + solid wood (MET +W)

	ZGBI White embossed painted RAL 9010	+		Transparent varnished natural ash
	ZGNE Black embossed painted RAL 9005	+		Transparent varnished natural ash

metal beams

	ZGBI White embossed painted RAL 9010		ZGNE Black embossed painted RAL 9005
---	--------------------------------------	---	--------------------------------------

top finish

melamine

	MBI White		MWP Pearl white		MTR Dove-grey
	MCE Concrete		MOB Light elm		MRO Oak
	MNC Walnut		MFN Black ash		MNV Black velvet

melamine with colour-contrasting edge



GMBI – White with green grey edge



NMBI – White with black edge



BMOB – Light elm with white edge



GMOB – Light elm with green grey edge



NMOB – Light elm with black edge



GMNC – Walnut with green grey edge



NMNC – Walnut with black edge



GMNV – Black velvet with green grey edge

OPTIONAL

1. front screen

melamine: made of 18-mm-thick chipboard (density 720 kg/m³, formaldehyde emission compliant with EU Regulation 2023/1464 and EPA TSCA Title VI), faced with anti-reflex melamine resins, edged with ABS (2-mm thick with radiused edges). It features a standard milling on the lower side for the insertion of the accessory bar (in this case the screen must be rotated 180°). The height of the screen from the desk top is 15" 1/8. A space of 5/8" remains between the screen and the top for cable passage. The front screens are fixed to two clamps. There are two types of clamps: 1) clamps with under-top fixing for screens without a central profile; 2) clamps with fixing above the central profile for screens with a central profile (in this case, cable passage is not permitted). The height reached by the screen is the same in both cases.

Front screen: W. 39" 3/8 / 47" 1/4 / 55" 1/8 / 63" / 70" 7/8 / 78" 3/4 D. 3/4" H. 15" 1/8.

fabric: made of 18 mm thick fabric-covered chipboard (density 720 kg/m³, formaldehyde emission compliant with EU Regulation 2023/1464 and EPA TSCA Title VI). The screen has a milling on the top, hidden under the fabric covering, for the insertion of an accessory bar. The fabric has to be torn in correspondence with the milling in order to insert the bar. The height of the screen from the desk top is 15" 1/8. A space of 5/8" remains between the screen and top for cable routing. The front screens are fixed to two clamps. There are two types of clamps: 1) clamps with under-top fixing 2) clamps with fixing above the central profile. The height reached by the screen is the same in both cases.

Front screen: W. 39" 3/8 / 47" 1/4 / 55" 1/8 / 63" / 70" 7/8 / 78" 3/4 D. 3/4" H. 15" 1/8.

glass: made of 6 mm thick tempered glass according to EN12150 with flat polished edges, etched on both sides. There is a 7/8" space between the screen and the top for cable passage. The front screens are fixed to two clamps. There are two types of clamps: 1) clamps with under-top fixing 2) clamps with fixing above the central profile. The height reached by the screen is the same in both cases.

Front screen: W. 39" 3/8 / 47" 1/4 / 55" 1/8 / 63" / 70" 7/8 / 78" 3/4 D. 1/4" H. 15" 1/8

2. intermediate and ending side screens

melamine: made of 18-mm-thick chipboard (density 720 kg/m³, formaldehyde emission compliant with EU Regulation 2023/1464 and EPA TSCA Title VI), faced with anti-reflex melamine resins, edged with ABS (2-mm thick with radiused edges). It features a standard milling on the lower side for the insertion of the accessory bar (in this case the screen must be rotated 180°). The height of the screen from the desk top is 15" 1/8. The intermediate side screens are fixed to the top by means of a steel sheet support, while the end side screens are fixed to the top by means of a clamp fitted under the top with a steel plate.

Intermediate side screen: W. 31" 1/2 D. 3/4" H. 15" 1/8

End side screen: W. 31" 1/2 / 49" 1/4 / 65" D. 3/4" H. 15" 1/8

fabric: made of 18 mm thick fabric-covered chipboard (density 720 kg/m³, formaldehyde emission compliant with EU Regulation 2023/1464 and EPA TSCA Title VI). The screen has a milling on the top, hidden under the fabric covering, for the insertion of an accessory bar. The fabric has to be torn in correspondence with the milling in order to insert the bar. The height of the screen from the desk top is 15" 1/8. The intermediate side screens are fixed to the top by means of a steel sheet support, while the end side screens are fixed to the top by means of a clamp fitted under the top with a steel plate.

Intermediate side screen: W. 80 D. 3/4" H. 15" 1/8

End side screen: W. 49" 1/4 / 65" D. 1/4" H. 15" 1/8

glass: made of 6 mm thick tempered glass according to EN12150 with flat polished edges, etched on both sides. There is a 7/8" space between the screen and the top for cable passage. The side end screens are secured to the top using a clamp fixed underneath the top with a steel plate.

End side screen: W. 31" 1/2 / 49" 1/4 / 65" D. 1/4" H. 15" 1/8

3. sound-absorbing screen	30 mm thick panel with recycled polyester fibre interior (average density 50 kg/m ³), edged on three sides with 1 cm thick forex reinforcement. Base in 3x3 cm shaped plywood with sockets for the insertion of the fixing hardware. The panel is then covered in fabric and fixed to the base with metal clips. Total thickness 1" 1/4. W. 39" 3/8 / 47" 1/4 / 55" 1/8 / 63" / 70" 7/8 / 78" 3/4 D. 1" 1/4 H 15" 1/8
4. central profile for screens	extruded profile (D. 1" 3/4 H. 3/4") in anodised aluminium, closed at the ends by a pair of transparent ABS end caps. Fixed to a pair of brackets (W. 15" 3/4 D. 1" 5/8 H. 5/8"), made of 2 mm thick powder-coated steel sheet, with metric screws and nuts inserted in the corresponding recesses. Inside the recess there are slotted through holes for attaching the screens.
5. hand-pad	1.5 mm thick steel sheet covered in eco-leather. W. 31" 1/2 P. 19" 3/4
6. hanging drawer	consisting of structure, drawer and front made of 0.8 mm thick steel sheet painted with powders in an embossed finish. The drawer slides on damped ball bearing runners with partial extension. The bottom is equipped with 4 threaded inserts for attaching the helmet/bag holder. The maximum load capacity is 6.6 lbs. Useful internal dimensions: L. 13" 1/4 P. 14" 1/2 H. 2" 3/4; External dimensions: L. 16" 1/2 P. 15" 3/8 H. 4".
7. helmet/bag holder	made of 1.2 mm thick steel sheet painted with powder with an embossed finish. Fastened to the lower part of the drawer structure with metric screws. The back is 3" 7/8 high. Maximum load capacity is 17,6 lbs. W. 16" 1/2 D. 14" 3/4 H. 12" 5/8.
8. accessory bar	consisting of an extruded aluminium bar and supplied with 3 caps (2 end caps and 1 intermediate cap) made of ABS. W. 39" 3/8 / 47" 1/4 / 49" 1/4 / 55" 1/8 / 63" / 65" / 70" 7/8 / 7" 7/8 D. 3/4" H. 1/4"
9. document holder	made of 1 mm thick folded steel sheet, powder coated with an embossed finish and open on the front side. It does not require fastening as it is shaped to hook onto the accessory bar. W. 13" D. 9" H. 7" 7/8.
10. shelf for document holder	1 mm thick steel sheet, bent and powder-coated with and embossed finish. To be placed on dox holder. W. 13" D. 9" H. 3" 7/8.
11. stationary tray	1 mm thick steel sheet folded and powder coated with an embossed finish. Does not require fastening as it is shaped to hook onto the accessory bar. W. 11" 3/4 D. 3" 7/8 H. 1".
12. A4 paper tray	made of 1 mm thick steel sheet, folded and powder coated and open on the front side. It does not require fastening as it is shaped to hook onto the accessory bar. W. 13" D. 9" H. 2".
13. objects tray	made of 1 mm thick steel sheet, folded and powder coated with an embossed finish. It does not require fastening as it is shaped to hook onto the accessory bar. W. 5" 1/8 D. 3" 7/8 H. 3" 7/8.
14. CPU holder	(PCPU01) made of 1 mm thick steel sheet, folded and powder-coated with an embossed finish. Fixed to the top with wooden screws. The maximum load capacity is 22 lbs. W. 8" 5/8 D. 19" 3/4 H. 21" 7/8.
15. height and width-adjustable CPU holder	(EEPCA) consisting of a plastic-coated metal supporting structure, base and side supports to hold the computer case in place. Comes with an upper bracket to secure it to the work surface using wooden screws. The side and top supports are adjustable to fit different case sizes. Height adjustment (internal space): 15" 3/8 to 21" 1/4; Width adjustment (internal space): 5" 1/8 to 9". The maximum load capacity is 66 lbs.
16. top access	<u>metal</u> : made of powder-coated aluminium with two self-extinguishing thermopolymer closing elements. The upper part features an powder-coated aluminium door and a dust cover profile. The door can be hinged open only on one side. W. 12" 1/2 D. 4" 3/4 H. 1"
17. cable tray	made of 1 mm thick U-shaped powder-coated steel sheet. The tray interlocks with the top access frame. Fitted with holes on the lower side that can be used for attaching multiple-plug sockets (by means of screws or clamps, not included) or for earthing (by screwing the cable lug for earthing with screw and bolt, not included).

	W. 11" 3/8 D. 3" 3/4 H. 3" 7/8.
18. height-adjustable cable tray	made of 1 mm thick steel sheet painted with powders with an embossed finish and open on the sides to allow cable routing to adjacent locations. On the underside there are 4 holes (Ø 2" 1/8) for grounding the cables and other holes that can be used for attaching multiple-plug sockets (by means of screws or clamps, not included) or for earthing (by screwing the cable lug for earthing with screw and bolt, not included). Each side is equipped with two sets of slots at a pitch of 5/8" for attaching the supporting brackets and allowing them to be adjusted in height. The supporting brackets are made of 1.5-mm-thick epoxy-powder-coated steel plate and are attached to the beams. Side end caps, made of 1 mm thick epoxy powder-coated steel sheet with an embossed finish, are available on request and can be attached to the tray. Tray - top distance: 3" 1/4 to 4" 7/8 (depending on the setting) W. 39" 3/8 / 47" 1/4 / 55" 1/8 / 63" / 70" 7/8 D. 13" 3/8 H. 27" 9/8
19. vertical cable duct	composed of a 3 mm thick folded powder coated steel sheet base (W. 5' 7/8 D. 5' 7/8 H. 1/4") and a series of rectangular plastic elements (W. 2" 1/2 D. 1" 5/8 H. 1" 1/8) joined together to guide the cables to the top. For each vertebra there are 45 elements (H. max. 33" 1/8). At the end there is an element for fixing the vertical cable management to the top (using self-tapping wood screws).
20. carter for vertical cable management	consisting of a 1 mm thick folded steel sheet base, powder-coated with an embossed finish. 2 magnets with a diameter of 3/4" are located in the hollow part for direct attachment to the metal leg. W. 2" D. 1" H. 22"
21. removable carter (for intermediate leg)	made of 1 mm thick powder-coated steel plate and fitted with hooks for attachment to the middle of the legs. A space of 1" 5/8 remains between the floor and the lower edge of the carter to allow for the passage of cables. The same space is available at the top between the leg beam and the upper edge of the carter. W. 6" 1/2 D. 2" H. 23" 1/4.
22. central cover	in 1.2 mm thick powder-coated steel plate. The cover hooks onto a pair of 1.5 mm thick sheet steel plates (W. 6" 1/8 D. 1" 1/8) fixed under the top with metric screws. W. 39" 3/8 / 47" 1/4 / 55" 1/8 / 63" / 70" 7/8 / 78" 3/4 D. 1" 1/8 H. 3/4"
electrification	the desk can be equipped with the following electrification: VERSATEK – ALUPOWER – VERSALIFT – LID FOR CABLE OUTLET – MULTISOCKET (please refer to the electrification section for more specifications).

ABACUS | Bench

Free-standing module

2 persons bench




4 persons bench




Hanging bench

2 persons bench desk for attachment to 2 H. 29" 1/8 cabinets




2 persons bench for 2 supporting service units




2 persons bench desk for attachment to 4 H. 29" 1/8 cabinets



2 persons bench desk for attachment to 2 H. 29" 1/8 cabinets e and 2 supporting service units



2 persons bench desk for attachment to 4 supporting service units



Bench for compositions INITIAL

2 persons initial bench




2 persons initial bench desk with
profile for side screen




1 person initial desk




1 person initial desk with profile for
side screen




2 persons initial bench for
attachment to 2 H. 29"1/8 cabinets




2 persons initial bench desk with
profile for side screen for attachment
to 2 H. 29"1/8 cabinets



2 persons initial bench for 2
supporting service units



Initial bench with profile for side
screen for 2 supporting service units



INTERMEDIATE

2 persons intermediate bench



2 persons intermediate bench with
profile for side screen



ENDING



2 persons ending bench




1 person ending desk



2 persons bench desk for attachment
to 2 H. 29"1/8 cabinets



2 persons bench for 2 supporting service units



RIBA


2 persons bench




4 persons bench





2 persons bench desk for attachment to 2 H. 29"1/8 cabinets





2 persons bench for 2 supporting service units




2 persons bench desk for attachment to 4 H. 29"1/8 cabinets



2 persons bench desk for attachment to 2 H. 29"1/8 cabinets e and 2 supporting service units



2 persons bench for 4 supporting service units



Bench for composition - RIBA

INITIAL

2 persons initial bench




2 persons initial bench with profile for side screen



1 person initial desk





1 person initial desk with profile for screen



2 persons initial bench for attachment to 2 H. 29"1/8 cabinets



2 persons initial bench with profile for side screen for attachment to 2 H. 29"1/8 cabinets



2 persons initial bench for 2 supporting service units



INTERMEDIATE

2 persons intermediate bench




ENDING

2 persons ending bench




2 persons ending bench for 2 supporting service units



2 persons initial bench with profile for side screen for 2 supporting service units





2 persons intermediate bench with profile for side screen



1 person ending desk





Bench finale 2 posti per aggancio a 2 contenitori H. 74 cm





ABACUS | Optionals



1. front screen



Melamine




fabric




glass


front screen for central profile



melamine




fabric




glass


side screens for central profile




2. intermediate side screens



fabric W. 31"1/2




melamine W. 31"1/2



ending side screens




melamine




fabric




glass




3. sound-absorbing screen




4. central profile




5. hand-pad



6. hanging drawer




7. helmet/bag holder




8. accessory bar




9. document holder




10. shelf for document holder




11. stationary tray




11. A4 paper tray




12. objects holder




13. CPU holder




15. height-adjustable CPU holder




16. top access




17. cable tray




18. height-adjustable cable tray




19. vertical cable management



20. carter for vertical cable management



21. removable carter
(for intermediate leg)



22. central cover

